

# LPG Inert® IG-55

- Natural gas present in the atmosphere
- Design in compliance with ISO 14520, NFPA 2001 and CEA 4008
- Suitable for occupied areas
- Electrically non-conductive
- No residue to clean up after the discharge
- More economical and less storage space
- Zero Ozone Depletion Potential
- No greenhouse effect
- No decomposition products

**LPG INERT® IG-55** is a mixture with 50% ARGON (IG-01) and with 50% NITROGEN (IG-100). It is an inert gas, non-conductive, colourless, odourless and flavourless. It is non corrosive and may be used at normal temperatures with such materials as nickel, steel, stainless steel, copper, brass, bronze and plastics.

Perfect dielectric and appropriate for the protection of all the electric and electronic materials.

Discharge is through valves fully developed by **LPG** approved by the most renowned independent organizations. They offer a great flexible adaptability for all actuation and release systems currently used in the market, even allowing combinations of several of them.

The design of the system protects against accidental actuation due to any small leak. They also allow checking and maintenance of all critical elements contained in a fixed extinguishing system, at the time of commissioning and later for system preventive maintenance, thus preventing the risk of accidental discharge. As a general rule, extinguishing concentration is achieved when oxygen contents in the air is reduced from its usual level of 20,9% to values lower than 15% depending on the combustible products.

The natural extinguishing agent



VdS

VdS  
Schadenverthutung  
Vertrauen durch Sicherheit



Agencia Protección Contra Incendios  
Ministerio del Interior



Centre National de Prevention et Protection



VNIPO  
Russian Certification Body



Loss Prevention Certification Board





**LPG INERT® IG-55** is stored in high-pressure cylinders in the form of compressed gas, thus space required for such cylinder storage depends on pressure and capacity.

**IG-55** fire extinguishing systems are designed for a cylinder filling pressure of 150/200/300 bar. **LPG** uses Cylinders of 80 lt. and 140 lt. capacity, thereby, optimizing in space and cost.

**LPG INERT® IG-55** systems can be modular or centralized (single or double row). The system with manual or automatic release includes  $\pi$  (PI) certified bottles, equipped with a pressure gauge valves.

**LPG INERT® IG-55** is safe for use in occupied areas and excellent visibility is maintained during discharge. Ideal for the protection of archives, museums, libraries and any other hazard including valuable or unique property. Likewise it is suitable for the protection of computer rooms, telephone exchange equipment and any other electrical installation that may present a fire hazard.

## Physical Properties

Chemical name:	
Nitrogen/Argon	
Chemical formula :	
$N_2/Ar$	
Denomination according to ISO 14520 and NFPA 2001:	
IG-55	
Molecular weight :	
33.95	
Boiling point at 1.013 bar:	
-196° C	
Maximum filling pressure:	
150/200/300 bar	
Design concentration for heptane:	
47.5%	
Flooding factor for heptane at 20° C :	
0.633 m <sup>3</sup> /m <sup>3</sup>	
Design concentration for class A fires (NFPA):	
37.2%	
Flooding factor for class A fires (NFPA):	
0.457 m <sup>3</sup> /m <sup>3</sup>	
NOAEL:	
43%	
LOAEL:	
52%	
Maximum concentration in a 5' exposure:	
43%	
Ozone depletion potential :	
0	
Greenhouse effect potential :	
0	

### HEADQUARTERS

Mestre Joan Corrales, 107-109 08950 Esplugues de Llobregat  
- BARCELONA  
Tel.: +34 93 480 29 25 - Fax: +34 93 473 74 92  
e-mail: lpg@lpg.es - www.lpg.es

### EXPORT DEPARTMENT

Tel.: +34 93 480 29 33 - Fax: +34 93 473 74 92  
e-mail: export@lpg.es

## TOPAZ FIRE SYSTEMS (P) LTD.

No. 143/B7 (Part)  
Bommasandra Industrial Area,  
Bangalore - 560 099.  
Tel.: +91 080 41658921  
e-mail: info@topazfiresystems.com  
Web.: www.topazfiresystems.com