

Fire Fite® CO₂ fire extinguishers are suitable for fires involving materials like inflammable liquids, gaseous and electrical fires, oil spillages etc. They are ideal to handle live delicate machinery, flammable liquids, sensitive equipments & gases.

It extinguishes fire by blanketing, dilution of oxygen and cooling effect involving high voltage electrical equipment. Specialised CCOE Approved Cylinder & ISI Marked (IS 7285), CCOE Valves & ISI MARKED (IS 3224)

Available in Screw Down or Squeeze Grip Type Valve.

2A Portable CO₂ Type Fire Extinguishers



Fire Fite® brand CO₂ type fire extinguishers are suitable for fires involving materials like inflammable liquids, gaseous, oil spillages and electrical fires etc. They are ideal to handle live delicate machinery, flammable liquids and gases.



SPECIFICATION IS 15683 : 2006

CAPACITY	2 KGS	3 KGS	4.5 KGS
THICKNESS (MIN)	3.5 mm	4.2 mm	4.2 mm
DIAMETER	108 mm	139.8 mm	139.8 mm
HEIGHT	470 mm	435 mm	610 mm

PERFORMANCE

DISCHARGE TIME	8-18sec.	8-18sec.	8-18sec.
DISCHARGE % (MIN)	95	95	95

FIRE RATINGS	8B	8B upwards	13B
--------------	----	---------------	-----

TEMPERATURE RATING	-30°C to +55°C		
--------------------	----------------	--	--

All our fire ratings are higher than the minimum

Higher fire rating extinguishers can be provided



2B Trolley Mounted CO₂ Type Fire Extinguishers

SPECIFICATION IS 2878



CAPACITY	6.5 KGS	9 KGS	22.5 KGS	45 KGS
THICKNESS	4.2 mm	4.2 mm	5.5 mm	6 mm
DIAMETER	139.8 mm	139.8 mm	232 mm	267 mm
HEIGHT	865 mm	1120 mm	1030 mm	1520 mm
PERFORMANCE				
DISCHARGE TIME	8-18sec.	8-30sec.	12-30sec.	15-35sec
DISCHARGE % (MIN)	95	95	95	95
TEMPERATURE RATING		-30°C to +55°C		

All our fire ratings are higher than the minimum

Higher fire rating extinguishers can be provided