



FireFite® Mechanical Foam type fire extinguishers are useful for fires involving materials like oil, petroleum products, solvents, grease, paint etc.

It extinguishes fire by blanketing and cooling effect.

4A Portable (Stored Pressure)

CAPACITY	9 LTRS
SPECIFICATION	IS 15683 : 2006

DIMENSIONS

THICKNESS	1.6 mm
DIAMETER	175 mm
HEIGHT	570 mm
GROSS WEIGHT (APPROX)	12.5Kgs

PERFORMANCE

DISCHARGE TIME	45-70 sec
DISCHARGE % (MIN)	85
JET LENGTH	Actual 6m (Req (2 m)

FIRE RATINGS	2A 13B
--------------	--------

TEMPERATURE RATING	+5°C to +55°C
--------------------	---------------



All our fire ratings are higher than the minimum

Higher fire rating extinguishers can be provided

**Capacities:
2Ltrs, 4Ltrs, 6Ltrs & 9Ltrs**

4B Portable (Squeeze Grip Cartridge Type)

CAPACITY	9 LTRS
SPECIFICATION	IS 15683 : 2006

CAPACITY	9 LTRS
----------	--------

THICKNESS	1.6 mm
DIAMETER	175 mm
HEIGHT	570 mm
GROSS WEIGHT (APPROX)	12.5Kgs
CARTRIDGE CAPACITY	60 gms

PERFORMANCE

DISCHARGE TIME	45-70 sec
DISCHARGE % (MIN)	85
JET LENGTH	Actual 6m (Req (2 m)

FIRE RATINGS	2A 13B
--------------	--------

TEMPERATURE RATING	+5°C to +55°C
--------------------	---------------

**All our fire ratings are higher than the minimum
Higher fire rating extinguishers can be provided**



These extinguishers are equipped with specialised caps with controlled mechanism

Capacities :
2Ltrs, 4Ltrs, 6Ltrs & 9Ltrs

4C Trolley Mounted

CAPACITY	50 LTRS
----------	---------

SPECIFICATION	IS 13386
---------------	----------

DIMENSIONS

THICKNESS	3.15 mm
DIAMETER	300 mm
HEIGHT	1130 mm
GROSS WEIGHT (APPROX)	86 Kgs

PERFORMANCE

DISCHARGE TIME	60-180 sec
DISCHARGE % (MIN)	90
JET LENGTH	10 m

TEMPERATURE RATING	+5°C to +55°C
--------------------	---------------

**All our fire ratings are higher than the minimum
Higher fire rating extinguishers can be provided**



**Capacities: 50, 150 Ltrs and
with trailers also available.**