

6A Portable (Stored Pressure)

CAPACITY 9 LTRS
SPECIFICATION IS 15683: 2006

DIMENSIONS	
THICKNESS	1.6 mm
DIAMETER	175 mm
HEIGHT	570 mm
CARTRIDGE	60 Gms
GROSS WEIGHT (APPROX)	12.5Kgs
PERFORMANCE	
DISCHARGE TIME	45-70 sec
DISCHARGE % (MIN)	85
JET LENGTH	Actual 6m (Req (2 m)
<u> </u>	<u> </u>

FIRE RATINGS 2A

TEMPERATURE RATING +5°C to +55°C

All our fire ratings are higher than the minimum

Higher fire rating extinguishers can be provided



Capacities: 2Ltrs, 4Ltrs, 6Ltrs & 9Ltrs

A III CE IRS

6B Portable (Squeeze Grip Cartridge Type)

CAPACITY 50 LTRS

SPECIFICATION IS 15683: 2006

DIMENSIONS

THICKNESS 1.6 mm
DIAMETER 175 mm
HEIGHT 570 mm
CARTRIDGE 60 Gms
GROSS WEIGHT (APPROX) 12.5Kgs

PERFORMANCE

DISCHARGE TIME 45-70 sec
DISCHARGE % (MIN) 85
JET LENGTH Actual 6m (Req (2 m)

FIRE RATINGS 2A

TEMPERATURE RATING +5°C to +55°C

All our fire ratings are higher than the minimum Higher fire rating extinguishers can be provided





These extinguishers are equipped with specialised caps with controlled mechanism

Capacities: 2Ltrs, 4Ltrs, 6Ltrs & 9Ltrs

6C Trolley Mounted

CAPACITY 50 LTRS

SPECIFICATION IS 15683 : 2006

DIMENSIONS

THICKNESS 3.15 mm
DIAMETER 300 mm
HEIGHT 1130 mm
CARTRIDGE/ CYLINDERS 300 / 1Kgs
GROSS WEIGHT (APPROX) 86 Kgs

PERFORMANCE

DISCHARGE TIME 60-180 sec
DISCHARGE % (MIN) 90
JET LENGTH 10 m

TEMPERATURE RATING +5°C to +55°C

All our fire ratings are higher than the minimum Higher fire rating extinguishers can be provided



Capacities: 50Ltrs & 150 Ltrs

